

## Platform

1.33 m x 0.70 m aluminium platform

Slide bar rear entry

Footswitch

Full proportional control

1.43 m articulating jib

Remote control (via cable to platform)

Multi-lingual LCD display in on remote console

Platform console position interlock

## Functional Equipment & Accessories

Black low profile rubber tracks

Padded outriggers with cylinder rod protection

Automatic stabilization

Platform load sensing with automatic work envelope restriction (200kg/120kg)

Double emergency stop control

Auto cut-out when out of level

Three emergency descent functions

Plus 1° non-continuous rotation

Alignment assistance

## Available Options

90 AH/48V electric engine with Lithium battery package including battery charger.

Hatz 1B40 7.5HP – 5.0KW diesel engine

2<sup>nd</sup> travel speed (2.8 km/h)

180 x 72 x 37 mm low profile non-marking tracks

Single person platform 0.77 m x 0.60 m

## Power & Transmission

Electric engine  
2,2 KW – 110V/220V – 50Hz

Honda iGX440 15HP – 11 kW petrol engine

Engine protection



**JLG Industries Inc.**  
Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel: +31 (0)23 565 5665  
Fax: +31 (0)23 557 3750  
e-mail address: europe@jlg.com  
[www.jlgeurope.com](http://www.jlgeurope.com)  
An Oshkosh Corporation Company

Printed in Belgium  
FORM No.: DSX19J  
PART NO.: DSX19J-ENGLISH



