

Platform

1.33 m x 0.70 m
aluminium platform

Slide bar rear entry

Footswitch

Full proportional control

1.43 m articulating jib

Remote control
(via cable to platform)

Multi-lingual LCD display in on
remote console

Platform console position interlock

Functional Equipment & Accessories

Black low profile rubber tracks

Padded outriggers with cylinder
rod protection

Automatic stabilization

Platform load sensing with
automatic work envelope restriction
(200kg/120kg)

Double emergency stop control

Auto cut-out when out of level

Three emergency descent functions

Plus 1° non-continuous rotation

Alignment assistance

Available Options

90 AH/48V electric engine with Lithium
battery package including battery
charger.

Hatz 1B40 7.5HP – 5.0KW
diesel engine

2nd travel speed (2.8 km/h)

180 x 72 x 37 mm low profile
non-marking tracks

Single person platform
0.77 m x 0.60 m

Power & Transmission

Electric engine
2,2 KW – 110V/220V – 50Hz

Honda iGX440 15HP – 11 kW
petrol engine

Engine protection



JLG Industries Inc.
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 3750
e-mail address: europe@jlg.com
www.jlgeurope.com
An Oshkosh Corporation Company

Printed in Belgium
FORM No.: DSX19J
PART NO.: DSX19J-ENGLISH



120 kg (restricted) 200 kg (unrestricted)

¹ Certain options or country standards may increase weight and/or dimensions.

