



STEIGER® T 700 HF



70 m working height with not even 12 m vehicle length! Extremely compact, manouevrable and always operational







TOP PERFORMANCE DATA*










83° angle of elevation

Registration possible with 32 t (up to 36 t)

*depending on chassis and equipment



→ Always ready for use











More flexibility in use, also under narrow conditions (projecting edges, foreparts)



TOTAL UPPER BOOM OUTREACH

+3.5 m more as on the T 650 HF



Inflexion point + 1.7 m

more effective "up, over and back" working




Easy and flexible working

Optimised utilisation of the outreach: Overhangs can simply be bridged; it can at the same time be worked close to the object



Three-fold upper boom

for more manoeuvrability

















THREE-FOLD UPPER BOOM FOR MORE MANOEUVRABILITY

- Double effect: Compact in retracted state and high outreach thanks to the three-fold upper boom
- Optimal straightening with small place requirement

EVEN MORE UNDERFLOOR PERFORMANCE

- Underfloor working possible up to 17 m
 + 5 m more than the competition
- Effective use due to the 440° basket rotation angle
- Thanks to the additional movable RÜSSEL® ideal for bridge inspections











220°

Real rotating angle of the RÜSSEL®'s by optimised basket boom articulation

10° MORE



2.0 m RÜSSEL® length

therefore 6 m flexibility on the object




40° MORE RÜSSEL® rotation



Standing working basket ideal for "under and up" as well as all possibilities of "up and over and back" with lowered RÜSSEL®



Significantly MORE flexibility in use, with the https://doi.org/10.2581/big.10.2










More flexibility in use with the highflexBASKET

- Maximum basket rotating angle
- 🕂 2 x 220° basket rotation
- Largest basket on the market
 3.82 m x 0.97 m extended
- 🔂 600 kg basket load
- Less disruptive factors in the basket
- All positions also possible with extended basket



New construction with even more features and optional extras




- Stable design, reinforced floor
- Barrier-free, heating, illuminated basket floor
- New lift-up system (+25 kg payload)
- Camera basket
- Material winch
- Basket floor lighting
- Movable folding seat
- More cleaning openings
- Periphery lighting and much more









CHASSIS CHOICE

- Permissible GVWR 32 36 t
- Types of drive 8 x 2, 8 x 4
- Axle combination 1-3
- Extremely compact front overhang
- Standard or long driver's cab
- Compact turning circle due to the axle combination 1-3 in connection with a steerable trailing axle
- High service availability throughout Europe























even MORE HEIGHTperformance advantages and features

PROVEN TECHNOLOGY AND FEATURES

- Stable boom system through proven profile with multiple edging of the high-tech steel
- 3-fold upper boom telescope, complete extendable also with 600 kg basket load
- Easy handling through same function and handling as with the previous STEIGER® large-scale models
- Full control stand at turret (option)
- U-plates mounted on the jacks
- COCKPIT (control unit in the basket)
- VARIOUS jack control stands basket vehicle rear (left + right) alternate control

- Component similarity to other models providing ADDED value
- In the procurement and stocking of spare parts
- For service / maintenance
- For storage / costs









USEFUL optional extras

MORE comfort MORE safety MORE efficiency









- Lift-up system for safe lifting of material in the basket
- Box attachments and bodies for safe carrying of plenty tools and material
- Generator
- Illuminating equipment on the vehicle / at the jacks, on and at the basket
- Heating systems for the COCKPIT control stand and basket floor
- First-aid kit in the basket

- Movable folding seat for the operator in the basket
- Camera fastening devices for TV productions
- Lower boom camera
- and much more.














DRS as optional extra

- Thanks to the RUTHMANN DRS, you dispose of previously unthinkable performance data
- The DRS generates more working range, more outreach and therefore more flexibility in use → more utilisation, turnover and quicker ROI
- On-Board outreach calculation in real time

DRS = MORE outreach



ADDITIONAL OPTIONS FOR THE DRS

SUPPORT LOAD ASSISTANCE SYSTEM

Work at 50 % support load

Each jack can individually be preset in 6 levels: 50 %, 60 %, 70 %, 80 %, 90 % and 100 % of the maximal support load.

WIND ASSISTANCE SYSTEM

Work at wind force 7 or 8

Adjust wind force before starting work. The DRS adjusts the possible outreach under the premise of the maximum basket stability.

BASKET PAYLOAD ASSISTANCE SYSTEM

Work in the basket with 600 kg

Simply preset the desired basket load.


3 selectable levels: deactivated, 320 kg or 600 kg.












Largest spare-parts warehouse with the fastest, worldwide spare-parts dispatch and highest delivery capacity

Highly professional, worldwide deployable service technician taskforce and video service

Market-leading information and diagnosis system in the state-of-the-art control panel "COCKPIT" for comprehensive worldwide remote diagnostic availability



















Extremely compact, manoeuvrable and always operational!

Does the RUTHMANN STEIGER® T 700 HF convince you? We would be pleased to provide you with more details.

Thanks a lot for your interest!



All data has been included without warranty. All measurements and weights are approximate and refer to the standard basic execution. Technical alterations reserved.

Advantages overview

- 70 m working height
- 41 m outreach
- Compact turning circle (11.99 m) due to the axle combination 1-3 in connection with a steerable trailing axle
- Extremely compact with minimal front overhang
- highflexRÜSSEL® → 220° movement range
- highflexBASKET → 440° rotating range
- Even longer upper boom
- Multi-chassis possibilities: brands, driver's cab types, types of drive (8x2, 8x4)
- Most recent control and operation technology (COCKPIT)
- Comprehensive optional extras
- Worldwide available service
- Numerous worldwide references

STEIGER® T 700 HF

Ruthmann Holdings GmbH

Ruthmannstraße 4 48712 Gescher GERMANY

Phone: +49 2863 204-0 Fax: +49 2863 204-212 Internet: www.ruthmann.de E-mail: info@ruthmann.de

